

Electrobomba H, V, V10 y V20
con variador incorporado

Con variador integrado
Con bancada
Con calderín de 5 lts. incluido



1 bomba trifásica a velocidad variable

Prestaciones y características

Tipo 1 bomba	Motor P2		l/min m³/h	15	30	45	60	75	90	120	150
	KW	HP		0,9	1,8	2,7	3,6	4,5	5,4	7,2	9
VARIVIP2 1H 81T	0,6	0,8	m.c.a.	39	36	31	25	17	6		
VARIVIP2 1H 101T	0,8	1		52	48	42	34	22	8		
VARIVIP2 1H 121T	0,9	1,2		64,5	60	52	42	28	10		
VARIVIP2 1H 150T	1,1	1,5		56,2	55	53	50	46	42	32	20
VARIVIP2 1H 200T	1,5	2		68,5	67	64	61	57	52	40	24,7

Tipo 1 bomba	Motor P2		l/min m³/h	15	30	45	50	75	90	120	150
	KW	HP		0,9	1,8	2,7	3	4,5	5,4	7,2	9
VARIVIP2 1V 15T	1,1	1,5	m.c.a.	56,8	55	53	50	46	42	32	20
VARIVIP2 1V 20T	1,5	2		68,5	67	64	61	57	52	40	24,7
VARIVIP3 1V 30T	2,2	3		81,5	79	76	73	68	64	49	30
VARIVIP3 1V 35T	2,2	3		95,2	92	88,5	85	79,2	74,5	57	35,5
VARIVIP3 1V 40T	3	4		109	105	101	97	90,5	85	65	41
VARIVIP3 1V 45T	3,3	4,5		120	116	110	105	97	90	72	48

Tipo 1 bomba	Motor P2		l/min m³/h	33	83	133	183	233	283	333	383
	KW	HP		2	5	8	11	14	17	20	23
VARIVIP2 1V10 20T	1,5	2	m.c.a.	31	29	27	23	18	12	2	
VARIVIP3 1V10 30T	2,2	3		40	38	36	31	26	18	8	
VARIVIP3 1V10 40T	3	4		64	62	58	54	46	35	18	8
VARIVIP3 1V10 55T	4	5,5		78	75	70	64	55	44	24	10
VARIVIP3 1V10 65T	4,7	6,4		89	85	80	73	63	50	27	12
VARIVIP3 1V10 75T	5,5	7,5		112	105	100	91	74	59	29	15

Tipo 1 bomba	Motor P2		l/min m³/h	50	150	250	300	350	400	450	500
	KW	HP		3	9	15	18	21	24	27	30
VARIVIP3 1V20 55T	4	5,5	m.c.a.	78	69	57	50	42	34	24	14
VARIVIP3 1V20 65T	4,7	6,4		90	81	67	58	49	40	28	16
VARIVIP3 1V20 75T	5,5	7,5		104	92	76	67	56	45	32	19

