

Abrazaderas de reparación de fundición maleable DC

Para tubos de acero:

DIN EN 10255 (antes DIN 2440/2441), DIN 2442 y DIN 2448/DIN 2458 fila 1, ISO 65



- Para conducciones de: Agua
- Temperaturas: Agua hasta +90 °C
- Medidas: 3/8"-4"
- Presión de trabajo: Agua PN 16

Diámetro
nominal

Código
artículo


uni. caja

3/8"	01.260.28.00	—
1/2"	01.260.28.01	5
3/4"	01.260.28.02	10
1"	01.260.28.03	10
1 1/4"	01.260.28.04	5
1 1/2"	01.260.28.05	3
2"	01.260.28.06	3
2 1/2"	01.260.28.07	—
3"	01.260.28.08	—
4"	01.252.28.09	—

Características:

DN	Tubo de acero Ø exterior [mm]	Peso [kg]	Dimensiones		
			~A [mm]	~B [mm]	~C [mm]
10	3/8"	0,2	70	28	53
15	1/2"	0.3	70	33	60
20	3/4"	1.4	70	40	70
25	1"	0.46	70	46	74
32	1 1/4"	0.64	80	57	86
40	1 1/2"	1.03	100	66	94
50	2"	1.27	100	80	109
65	2 1/2"	1.99	100	100	140
80	3"	2.38	100	115	150
100	4"	3.31	100	140	187