

Abrazaderas con derivación de fundición maleable DT


gebo[®]
ACERO

Para tubos de acero:

DIN EN 10255 (antes DIN 2440/2441), DIN 2442 y DIN 2448/DIN 2458 fila 1, ISO 65



- Para conducciones de: Agua
- Temperaturas: Agua hasta +90 °C
- Medidas: 3/8" - 4"
- Presión de trabajo: Agua PN 16

Diámetros x rosca	Código artículo	 uni. caja
3/8" x 3/8"	01.261.28.0000	10
1/2" x 1/2"	01.261.28.0101	15
3/4" x 1/2"	01.261.28.0201	15
1" x 1/2"	01.261.28.0301	15
1" x 3/4"	01.261.28.0302	15
1 1/4" x 3/4"	01.261.28.0402	8
1 1/2" x 3/4"	01.261.28.0502	6
2" x 1"	01.261.28.0603	4
2 1/2" x 1"	01.261.28.0703	
2 1/2" x 1 1/4"	01.261.28.0704	
2 1/2" x 1 1/2"	01.261.28.0705	
3" x 1"	01.261.28.0803	
3" x 1 1/4"	01.261.28.0804	
3" x 1 1/2"	01.261.28.0805	
3" x 2"	01.261.28.0806	
4" x 1"	01.261.28.0903	
4" x 1 1/4"	01.261.28.0904	
4" x 1 1/2"	01.261.28.0905	
4" x 2"	01.261.28.0906	

Características:

DN	Rosca ISO 7/1	Tubo de acero		Peso [kg]	Dimensiones				
		Ø exterior [mm]	rosca ISO 7/1		-A [mm]	-B [mm]	-C [mm]	-D [mm]	-E [mm]
10	3/8"	17,2	3/8"	0,2	70	28	53	36	22
15	1/2"	21,3	1/2"	0,4	70	33	60	50	31
20	3/4"	26,9	1/2"	0,4	70	40	70	55	32
25	1"	33,7	1/2"	0,48	70	46	74	61	37
			3/4"	0,55	70	46	74	61	37
32	1 1/4"	42,4	3/4"	0,67	80	57	86	75	45
40	1 1/2"	48,3	3/4"	1,1	100	66	94	85	48
50	2"	60,3	1"	1,4	100	80	109	100	60
65	2 1/2"	76,1	1"	2,1	100	100	140	115	65
			1 1/4"	2,1	100	100	140	115	65
			1 1/2"	2,1	100	100	140	115	65
80	3"	88,9	1"	2,5	100	115	150	131	75
			1 1/4"	2,5	100	115	150	131	75
			1 1/2"	2,5	100	115	150	131	75
			2"	3,2	135	115	150	136	75
100	4"	114,3	1"	3,4	100	140	187	160	90
			1 1/4"	3,4	100	140	187	160	90
			1 1/2"	3,4	100	140	187	160	90
			2"	4,4	135	140	187	165	90